

Specification Matrix - Select one option from each section

Slider Options for Specifying GLYDE™		Description	Code	Example	
Format	For single sliders up to 3.0h x 1.5w	Small Format with 50mm Deep Frame	SF50	SF50	F
	For single sliders up to 3.0h x 3.0w	Large Format with 50mm Deep Frame	LF50		
Track Type	Track is fixed to the face of a wall or bulkhead	Face Mounted	F	CV	A30
	Track runs into a cavity/pocket (constructed by others)	Cavity Mounted	C		
	Track is partially recessed into the ceiling	Recess Mounted	R		
Track Layout	For single or bi-parting sliders running along a single track line	Single	1	SF50 / F2B / CV / A30	Small Format Face Mounted Track Dual slider configuration Bi-parting pair (opening from the middle) Clear view (no mid rail) Acoustic rating of Rw30
	Dual slider configuration	Dual	2		
	Triple slider configuration	Triple	3		
Configuration	Opening from one end	One Way	O	CV	
	Opening from the middle *Note on spec if doors are to meeting at a 90° angle	Bi-Parting	B		
	Three way intersection (3 sliders meeting to form a T configuration)	T Intersection	T		
Panel Construction	For small format sliders up to 3.0m high x 1.5m wide	Clear View (no mid rails)	CV	1MR	
	For panels up to 2400h on Large format sliders	1 x Mid Rail	1MR		
	For panels over 2400h on Large format sliders	2 x Mid Rails	2MR		
Acoustics	Using single or dual track layouts	Acoustic - Rw30	A30	A30	
	Using single track layouts	Acoustic - Rw30 to Rw35	A**		
	Available in all configurations	Non Acoustic	NA		
		<i>*Dual & Triple configurations will impact acoustic performance of the systems</i>			

