

# GLYDE® Sliders Specification Matrix.

Select one option from each section

# GLYDE

	Slider Options	Description	Code
Format	Glazed Sliders	Glass construction	<b>SG50</b>
	Solid Sliders	Board construction	<b>SB50</b>
Track Type	Face Mounted	Track is fixed to the face of a wall or bulkhead	<b>F</b>
	Cavity Mounted	Track runs into a cavity/pocket (constructed by others)	<b>C</b>
	Recess Mounted	Track is partially recessed into the ceiling	<b>R</b>
Track Layout	Single	For single or bi-parting sliders running along a single track line	<b>1</b>
	Dual	Dual slider configuration	<b>2</b>
	Triple	Triple slider configuration	<b>3</b>
	Multi-stacking	Four to six panel slider configuration	<b>4</b>
Configuration	One Way	Opening from one end	<b>O</b>
	Bi-Parting	Opening from the middle <i>*Note on spec if doors are to meeting at a 90° angle</i>	<b>B</b>
	T Intersection	Three way intersection (3 sliders meeting to form a T configuration)	<b>T</b>
Panel Construction	Clear View (no mid rails or vertical mullions)	A butt joint will be incorporated into the glass for panels over 1.5m wide	<b>CV</b>
	1 x Mid Rail	For panels up to 2400h - can be used in place of a manifestation, powder coated to suit frames	<b>1MR</b>
	2 x Mid Rails	For panels over 2400h if vertical mullions are not suitable	<b>2MR</b>
	1 x Vertical Mullion	Panels over 2.5m wide may require vertical mullions if midrails are not suitable	<b>1VM</b>
	2 x Vertical Mullion	For panels over 3000mm wide (will accommodate widths of up to 5.0m for a single slider)	<b>2VM</b>
	Vertical H Rail	H Rail join between solid finishes	<b>VH</b>
Acoustics	Acoustic - Rw30, Rw32 or Rw35	* Board construction only available in Rw35	<b>A</b>
	Non Acoustic	* Dual & Triple configurations will impact the acoustic performance of the systems * GLYDE sliders have been tested in a Dual configuration achieving Rw32	<b>NA</b>

## Example

**SG50 R 2 O CV A32**

**SG50 / R20 / CV / A32**

Glazed Slider  
Recess Mounted Track  
Dual slider configuration  
Opening one way  
Clear view (no mid rail)  
Acoustic rating of Rw32

## Note:

- GASS (GLYDE Anti-Slam Systems) are fitted to all slider configurations on the closing operation.
- Also available for opening operation on particular configurations if required.
- DDA Certified Compliant systems - subject to weight limitations.

**Please contact a GLYDE Specification Manager to assist with your project requirements.**