



Notes:

1. FIXING:

14-10 Teks type 17. Fixing through bracket
45mm minimum embedment.

2. STRUCTURE:

Engineered structure by others.
JD3-F17 Hardwood Timber or
MPG10 Pine
Max packing by GLYDE 5mm

3. CAVITY

Full or partial lining of the cavity is recommended to prevent obstructing the slider and vision of the internals.
Internal Cavity dimension 90mm min.

GLYDE

GLYDE ARCHITECTURAL ACOUSTIC SYSTEMS

160 ORDISH RD, DANDENONG, VIC 3175
TEL: (03) 9798 4433
glydearchitectural.com.au

Product.

GLYDE - ACOUSTIC SLIDERS

PROPRIETARY

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALUMINIUM INDUSTRIES OF AUSTRALIA PTY LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ALUMINIUM INDUSTRIES OF AUSTRALIA PTY LTD IS PROHIBITED.

Description.

TRAILING STILE-CAVITY

DRAWN

AA

Date

13/11/2025

DRAWING NO.

GD-TD-0015

Revision

2